

IN THE CLAIMS:

Please cancel claims 2 and 5 without prejudice and amend claims 1, 3, 6, 9 and 11 as follows.

Sub 6
1. (Currently Amended) A clock generating method for an asynchronous transmission, comprising:

determining a plurality of actual signal arrival times;
averaging the plurality of actual signal arrival times; and
correcting a timing of a receiving clock on a basis of an average of the plurality of actual signal arrival times and an expected signal arrival time;

deriving an expected signal arrival time from the receiving clock; and
determining a frequency difference between a frequency corresponding to an average of the plurality of actual signal arrival times and a frequency of said receiving clock, and changing the frequency of the receiving clock according to said frequency difference.

2. (Canceled)

A
3. (Currently Amended) The method according to ~~claims~~ claim 1, wherein determining further comprises counting a time period between arrival of a first signal and arrival of a subsequent second signal.

4. (Previously Amended) The method according to claim 3, wherein averaging further comprises storing counted time periods and calculating an average of stored time periods.

5. (Canceled)

Sub E
6. (Currently Amended) The method ~~is~~ according to claim 1, wherein the asynchronous transmission is an ATM transmission and the signal is an ATM cell.

Cont
7. (Previously Amended) A clock generating apparatus for asynchronous transmission comprising:

means for determining an average of actual signal arrival times and for generating a control signal on a basis of a determined average of the actual signal arrival times and an expected signal arrival time; and

means for correcting a timing of a receiving clock on a basis of the control signal.

8. (Previously Amended) The apparatus according to claim 7, wherein the means for correcting comprises a voltage controlled oscillator.

9. (Currently Amended) The apparatus according to ~~claims~~ claim 7, wherein the means for determining comprises:

means for detecting an actual arrival time of a signal;

means for averaging a plurality of detected actual signal arrival times in order to obtain an average of the actual signal arrival times; and

means for comparing and correction control the average of the actual signal arrival times with the expected signal arrival time and for generating the control signal in accordance with a comparison result, wherein the expected signal arrival time is derived from the receiving clock.

10. (Previously Amended) The apparatus according to claim 9, wherein the means for determining comprises means for storing a plurality of detected actual signal arrival times.

11. (Currently Amended) The apparatus according to ~~claims~~ claim 9, wherein the means for detecting comprises a timer.

12. (Previously Amended) The apparatus according to claim 9, wherein means for comparing and correction control comprises a phase detector, and wherein a polarity of the control signal is changed in accordance with a result of comparison.

13. (Previously Amended) The apparatus according to claim 7, wherein the asynchronous transmission is an ATM transmission and the signal is an ATM cell.